FENTEC BATTERY OPERATOR

Omastream are excited to introduce the AXA Remote 2.0 by FENTEC™ to the New Zealand market.



The AXA Remote 2.0 by **FENTEC**^{∞} is like no other window opener and is the perfect solution for those hard to reach windows. It not only provides you with the ability to open them remotely, it is easily retrofitted and is battery operated allowing simple and cost effective installation.

It is important for people to have fresh and healthy air in their homes and the AXA Remote 2.0 provides a minimum ventilation capacity of 25 m3/hour per area, based on a window surface area of 0.26 m2. Due to its many opening possibilities, the AXA Remote 2.0 is also able to sufficiently ventilate an area of 22.5 m2.

It's like no other window opener you've seen before!

KEY FEATURES

- Simple and easy installation
- Easily retrofitted to existing windows
- Easy to combine with flyscreens
- Battery operated, no wiring required
- One remote can operate unlimited units
- Fully designed and manufactured in Europe

HIGH CLOSING STRENGTH

Thanks to an advanced closing system, where chain-tightening smoothly triggers the wedge lock, the window is closed with a tractive force of 400 N.

SELF-SUPPORTING

The AXA Remote 2.0 fully caters for its own power supply. Thus problematic and unattractive wiring is no longer necessary. The unit uses 4 AA penlight batteries and the remote control uses 2 AAA batteries.

SAFE LIVING

The AXA Remote 2.0 by **FENTEC™** is a very safe product. It uses more than 4 billion different codes and it is impossible for someone else to open your windows with another remote control.

PROGRAMMABLE

If your home has numerous windows, various units can be programmed to allow operation with a single remote control.

An unlimited number of units can be programmed in this manner.

Conversely, one closing unit can be operated by maximum 8 different remote controls.



The AXA Remote 2.0 features an anti-trap system that interrupts the closing movement.

If there is a risk of something becoming trapped between the window and the framework, the AXA Remote 2.0 will open.



FENTEC BATTERY OPERATOR

TECHNICAL SPECIFICATIONS

top-hung, casement and hopper windows minimum 30 x 38 cm (hxw) maximum 100 x 100 cm (hxw), with 1x AXA Remote 2.0

white or grey


Chain:


Tractive/closing force: Thrusting force: Type control signal:


Range remote control: and presence of light sources) and maximum 20 m 4 billion 4 AA batteries

Coding permutations:
Power supply unit:
Power supply remote control:
Movement cycles
per set batteries:

4.0 x 40 mm (9x)







Hinge side

ORDERING INFORMATION

PART NO.	DESCRIPTION	COLOUR
RF-AXA2.0 GY	FENTEC™ AXA Remote 2.0	GREY
RF-AXA2.0 WH	FENTEC™ AXA Remote 2.0	WHITE

